



7700 Series - New Construction Single Hung Vinyl Size

Size Chart & Standard Colonial Grid Configurations

Unit size	19 1/2"	23 1/2"	27 1/2"	31 1/2"	35 1/2"		39 1/2"	47 1/2"
Rough Opening	20"	24"	28"	32"	36"		40"	48"
35 1/2"	 1830V	 2030V	 2430V	 2830V	 3030V		 3430V	 4030V
37 1/2"	 1832V	 2032V	 2432V	 2832V	 3032V		 3432V	 4032V
43 1/2"	 1838V	 2038V	 2438V	 2838V	 3038V		 3438V	 4038V
47 1/2"	 1840V	 2040V	 2440V	 2840V	 3040V		 3440V	 4040V
49 1/2"	 1842V	 2042V	 2442V	 2842V	 3042V		 3442V	 4042V
53 1/2"	 1846V	 2046V	 2446V	 2846V	 3046V		 3446V	 4046V
59 1/2"	 1850V	 2050V	 2450V	 2850V	 3050V	59 3/4" 60 1/4"  3050EV*	 3450V*	 4050V*
61 1/2"	 1852V	 2052V	 2452V	 2852V	 3052V*		 3452V*	 4052V*
65 1/2"	 1856V	 2056V	 2456V	 2856V	 3056V*		 3456V*	 4056V*
71 1/2"	 1860V	 2060V	 2460V	 2860V*	 3060V*		 3460V*	 4060V*
73 1/2"	 1862V	 2062V	 2462V	 2862V*	 3062V*		 3462V*	 4062V*

- Drawings in this document are not to scale.
- Block and tackle balance
- Units in red meet or exceed the following:
 - Clear openable area $\geq$ 5.7sq.ft.
 - Clear openable width $\geq$ 20"
 - Clear openable height $\geq$ 24"
- Twins & Triples are continuous head / sill



WINDOWS
OUR SHIELD. YOUR GUARANTEE.

1-800-807-7006
www.7Dwindow.com